




India's Most Trusted CCTV Brand

UC-P422 S3 2MP IR BULLET NETWORK CAMERA



- 2MP (1920 × 1080) H.265 coding
- Max.resolution: 1920 × 1080
- ICR auto switch, true day / night
- 3D DNR, digital WDR, HLC, BLC, Defog and ROI coding
- 30~50m IR night view distance
- 1CH audio input
- Built-in micro SD card slot, up to 128GB
- DC12V/PoE power supply
- IP 67 ingress protection
- Support three streams
- Support mobile surveillance by smart phones and tablet PCs with iOS or Android OS
- Intelligent analytics



www.unicamsystems.com

SPECIFICATIONS

Model	UC-P422 S3
Specifications	
Camera	
Image Sensor	1 / 2.8" CMOS
Image Size	1920 × 1080
Electronic Shutter	1 s ~ 1 / 100000 s
Iris Type	Fixed Iris
Min. Illumination	0.0035 lux@F1.2,AGC ON; 0 lux with IR 0.009 lux@F1.6,AGC ON; 0 lux with IR
Lens	6 mm @F1.6, H.FoV: 86.1°, V.FoV:43.7°, D.FoV:103°
Focus	Fixed
Lens Mount	M12
Wide Dynamic Range	HWDR
BLC	Yes
HLC	Yes
Digital NR	3D DNR
Angle Adjustment	Pan: 0°-360°; Tilt: 0°-90°; Rotation: 0°-360°
Image	
Video Compression	H.265 / H.264
H.265 Compression Standard	Main Profile@Leve4.1 High Tier
Resolution	1080P (1920 × 1080), 720P (1280 × 720), D1, CIF, 480× 240
Main Stream	60Hz : 1080P(1 ~ 30fps) / 720P(1 ~ 30fps) 50Hz : 1080P(1 ~ 25fps) / 720P(1 ~ 25fps)
Sub Stream	60Hz : D1/CIF (1~30fps); 50Hz: D1/CIF (1~25fps)
Third Stream	60Hz : D1/CIF/480× 240 (1~30fps); 50Hz: D1/CIF /480× 240 (1~25fps)
Bit Rate	64 Kbps ~ 6Mbps
Bit Rate Type	VBR / CBR
Audio Compression	G711A / U
Image Settings	ROI, Saturation, Brightness, Hue, Contrast, Wide Dynamic, Defog, Sharpness, NR, etc. adjustable through client software or web browser
ROI	Each ROI to be configured separately
Interfaces	
Network	RJ 45
Audio	1CH audio input
Storage	Built-in micro SD card slot; up to 128GB
Reset	Yes
Functions	
Remote Monitoring	Web browsing, CMS remote control
Online Connection	Support simultaneous monitoring for up to 3 users; Support multi-stream real time transmission
Network Protocol	UDP, IPv4, IPv6, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, 802.1x, FTP, UPnP, HTTPS, HTTP, QoS
Interface Protocol	ONVIF
Storage	Network remote storage; micro SD card storage
Smart Alarm	Motion detection, SD card full, SD card error
Intelligent Analytics	Video blur detection, scene change detection, line crossing detection, region intrusion detection and object removal detection (object left/missing)
General Function	Watermark, IP address filtering, video mask, heartbeat, illegal login lock
PoE	Yes, IEEE802.3af
IR Distance	30 ~ 50 m
Ingress Protection	IP 67
Others	
Power Supply	DC12V / PoE
Power Consumption	< 7W

Operating Environment	- 30 °C ~ 60°C (-22°F~140°F) Humidity: less than 95 % (non-condensing)
Dimensions (mm)	217.8 × 80.5 × 80.3
Weight (net)	Approx. 0.65KG
Installation	Ceiling mounting; Wall mounting

DIMENSIONS

