



India's Most Trusted CCTV Brand

UC-P1009-2U

9POE+2FE 250M LONG DISTANCE POE SWITCH



FEATURES

- 9*10/100mbps POE port;2*10/100mbps Uplink port
- 250m Distance Vlan Support
- Support IEEE802.3AF/AT
- Whole Power:120W (52V 2.3A)
- All port supported by MDI/MDIX auto flip and self-negotiation
- Supply 8 10/100Mbps adaptive high speed forwarding data packet non-lost port.
- Support IEEE802.3x flow control for Full-duplex mode and backpressure for Half-duplex mode.
- Each port max. power supply reached 30W.

Application:

- Wireless Access Point
- IP Camera
- IP Phone
- Computer Networks

www.unicamsystems.com

SPECIFICATIONS

Product	9+2 Port 250m POE Switch (Built-in)
Model	UC-P1009-2U
POE Port	1 to 9 support IEEE802.3AF/AT Standard
Output Power	15.4W/30W IEEE802.3af/at
Power Pin	Both 1/2+、 3/6- and 4/5+7/8-
Whole Power	≤120W (52V 2.8A)
POE Protocol	IEEE 802.3af/IEEE 802.3at
POE Type	End-span
Power Distance	≤250m
Network Standard	IEEE 802.3、 IEEE802.3u、 802.3x、 802.3af/at
Network Medium	10/100BASE-TX:5 class and above non shielded twisted pair
Data Distance	≤250m
Switch Capability	1.6Gbps
Forwarding Mode	Store and forward
Forwarding Rate	10BASE-T:14880PPS/port 100BASE-tx: 14800pps/port
MAC Address	MAC address table 2K
Port Function	Power priority mechanism, fast and forward, MAC automatic learning and aging IEEE802.3X Full-duplex and mode and backpressure for Half-duplex mode
LED Indicator	LINK/ACT.100Mbps;POE Status Indicator; Power indicator; Extender
Working Environment	Working temperature : -10°-- 55℃
Weight	1.2kg
Size	200mm*118mm*44mm(L*W*H)