



India's Most Trusted CCTV Brand

Smart WiFi

4MP Indoor Dome Camera



Done Camera



UC-WF-4M-IR (PL)

ALL TIME COLOR CAMERA



4 MP
Resolutions



Cloud
Recording



256GB
SD Card



Auto Human
Tracking



2 Way Audio
Intercom



Wi-Fi



Works
with Alexa



All Time
Color Vision

FEATURES

- 4MP Wi-Fi Outdoor Dome Camera
- Built-in high-sensitivity MIC and speaker, support two-way audio
- Intelligent Human tracking, automatically tracking when people break area
- Support Micro SD Card Upto 256GB & Cloud Storage (Optional)
- Wi-Fi & Wired connection, scan the QR code to easily connect the camera
- Area motion detection, Humanoid detection, push alarm information
- Compression : H.264/H.265/H.265+



Infrared mode



Full-color mode

Technical Specification

| | | |
|------------------------------|---|--|
| Model Number | : | UC-WF-4M-IR (PL) |
| Image Sensor | : | 1/3" CMOS Sensor |
| Resolutions | : | 4MP: 2688 × 1520 |
| Video Compression Standard | : | H.264/H.265/H.265+ |
| Lens | : | 4mm @ F2.0, View Angle : 68° (Horizontal), 81° (Diagonal) |
| IR LED | : | 4 LED |
| IR distance | : | 30 Meter |
| White LED | : | 4 LED |
| White Distance | : | 20 Meter |
| Video Encode Stream | : | Main Stream : 2688 × 1520 \ 15FPS; Sub Stream : 640 x 360 \ 15FPS |
| Light Mode | : | Full color / Infrared / Intelligent |
| Audio Input \ Output | : | Supports Two-way Audio, Built-in Microphone and Speaker |
| Minimum Illumination | : | Color: 0.01Lux, Black and White: 0.001 Lux |
| Audio Compression Standard | : | AAC/G711A |
| WDR | : | Support DWDR |
| Electronic Shutter | : | Auto |
| Wi-Fi | : | IEEE802.11b, 802.11g, 802.11n |
| Frequency Range | : | 2.4 GHz - 2.4835 Ghz |
| Security | : | 64/128-bit WEB, WPA/WPA2, WPA-PSK/WPA2-PSK |
| RJ45 Network Port | : | RJ45 X 1(10M/100M Adaptive Ethernet Port) |
| Alarm | : | 1Motion Detection, Alarm Picture Push 2 Human Detection |
| Monitoring | : | Android & Iphone / Windows PC (EasyCloud) |
| Storage | : | Support Micro SD Card (Max 256GB) |
| Protocol | : | Proprietary Protocol NI/Onvif/RTSP |
| Power | : | DC12V/1A |
| Power Consumption | : | ≤15W |
| Working Temp | : | 0-15° RH Less Than 95% (No Condensation) |
| Storage Temperature/Humidity | : | -20° to 60° / 20% to 90% RH |
| Housing Type | : | Plastic |